



SAME CATEGORY RELATED ARTICLES



The Maxam Tire MS503 L5 Is Now Available in the 875/65R29 Size



Bandvulc's Gripmaster Range Praised as Top Quality Tyres by McGowan Grab Hire



Berco Hits the Road towards Environmental Impact Reduction



Spanish Company Moldtech Strengthens Its Position in Romania With 34 Meters Hydraulic Double Mould Delivery

use, Caprari's PM horizontal pumps series, built to withstand high pressures, have long stood as a reference point in the market, representing the best that current technology has to offer.

Thanks to their reliability, top performance and versatility of



These pumps can be used in the water industry, the drinking water sector, reverse osmosis snow-making and marine application. They are specially designed to be consistently durable, and to function in such a way that the need to replace wearable parts is kept to a minimum.

Their robust structure is resistant to mechanical stress, thanks to specially designed dimensions which allow for especially high performance and operation stability up to 100 bar of pressure.

High efficiency at the B.E.P, ensured by optimised geometry in the blade profiles of the impellers and diffusers, is one of the series' biggest strengths. Furthermore, wear is reduced to a minimum due to the fact that the hydraulics are equipped with an axial thrust compensation system.

The sizes of the hydraulics which make up the PM Series cover a wide range of flow rates and are available in CAST IRON, STAINLESS STEEL and DUPLEX.

It is exactly these PM machines, built for high pressures up to 100 bar, which benefit from the new size 65 hydraulic models. Depending on how the pump is going to be used, either a packing seal or a mechanical seal can be selected. The mechanical seal guarantees perfect regulation and protection against leakage, while the packing seal boasts superior ease of assembly and maintenance, reducing the risk of machine downtime.



The H version PM_65 with 4 poles is the configuration which allows for use with superheated water at temperatures of up to 120°C — though it is necessary to carry out checks on the 2 poles depending on the conditions the pump will be used in. The materials selected here guarantee durability even in such thermally heavy duty operating conditions. Vibration propagation is minimised in a great deal of operating conditions. As a result, barely any noise is created, which is a vital benefit especially when placing several machines at the same site.

Such reliability, top performance and versatility are the fruits of a great many years of experience in engineering, construction and application in the most diverse fields of use.



Chiara Angelino

TAG RELATED ARTICLES



John Deere Launches Its Biggest Trailed Model: The R975i Sprayer



Komatsu Reveals the Concept of the First Fully Electric and Remote-Controlled Mini Excavator

